



Water Leak Detection & Alarm System for Plenum Spaces

RS-096-MK6



FloodMaster's RS-096 simple water alarm system is designed to sound an audible alarm when the sensor puck comes in contact with just 1/16" of any non-flammable conductive liquid (such as water).

Wires directly to power source (120, 208 or 240V AC) via step-down transformer; mounting plate included. Ideal for plenum space installations, the kit also includes plenum-rated power and sensor wires and transformer mounting plate. An optional dry contact output to a home security panel, control room or appropriate relay is also standard on all units.

RS-096-MK6 SPECIFICATIONS

Cable Lengths:

Transformer Cable: 12'

Sensor Cable: 8'
(custom lengths also available)

Output Signal:

Connects to home security panel

Control secondary system with appropriate relay

SPDT relay output control

Use standard alarm wire

Transformer: 120, 208 or 240V AC to 24V AC with mounting plate

ORDERING INFORMATION

Valve Size	P/N	UPC
N/A	RS-096-MK6	857640005946

BENEFITS

- Audible alarm sounds with only 1/16" of water detected at the sensor puck
- Easy installation
- Additional sensor pucks can also be added to systems where a wider area of leak detection is required
- Dry contacts to interface with security systems

Typical Installations

Any plenum space where an undetected water leak could occur:

Drop ceilings

HVAC & chiller installations

Water heater tanks

Spaces above data processing centers

MA Board of Registration of Plumbers Approval Code # P1-0515-489.